



# vcloudpoint

Zero Client

<b>Model</b>	V1		
<b>Appearance</b>	<b>Size</b>	93(W)x90(D)x18(H) mm	
	<b>Weight</b>	150g	
	<b>Color</b>	Diamond black & moon sliver color	
<b>Configuration Methods</b>	Host side & Client side		
<b>Display Interfaces</b>	HDMI / VGA		
<b>Networking</b>	<b>Ethernet</b>	10/100/1000Mbps	
	<b>WIFI</b>	Optional external WIFI antenna: 802.11b/g/n	<b>Rear Panel</b>
<b>I/O</b>	<b>Display</b>	1×HDMI, 1×VGA	
	<b>USB</b>	4×USB 2.0	<b>Right Panel</b>
	<b>Network</b>	1×RJ45	
	<b>Audio</b>	1×microphone jack, 1×speaker jack	
<b>Anti-theft Gadget</b>	<b>Power</b>	1×5V DC	<b>Front Panel</b>
	<b>Switch</b>	1× power/reset switch	
	<b>Power Consumption</b>	5W	
<b>Resolution</b>	Normal display resolutions (32 bits @ 60Hz): 640×480, 800×600, 1024×768, 1280×1024, and 1600×1200  Wide display resolutions (32 bits @ 60Hz): 1360×768, 1366×768, 1440×900, 1600×900, 1680×1050, and 1920×1080		
<b>Audio</b>	16 bits, 44.1Khz/ 48Khz audio input / output via 3.5mm stereo jacks		
<b>Video</b>	Full HD 1080p for all media formats (Host side rendering for local and web-embedded videos on most media players; Client side rendering for local videos on VLC player 2.1.5 or newer versions.)		
<b>Supported USB</b>	Storage Devices, USB Hubs, Single, Multi-functional & Dot Matrix Printers, Smart Card Reader, Office & POS Scanners, Single Touch Screens, Ukeys, Parallel to USB Convertors, etc; An external power supply may be required for devices working on large voltage. View more USB devices at		
<b>Peripherals</b>	<a href="http://www.vcloudpoint.in">www.vcloudpoint.in</a>		
<b>Maximum number of users per shared host</b>	vMatrix Server Manager permits up to 99 users per shared host. Actual number of supported users depends on the host configuration and the type of applications used. View Host Configuration Guide at		
<b>Internal hardware</b>	<a href="http://www.vcloudpoint.in">www.vcloudpoint.in</a>		
	All solid-state design. No moving parts, no fans, no local user storage.		



<b>Data Security</b>	No local data storage on device. USB data access controlled by user policy.
<b>Environmental</b>	0 to 40 degrees Celsius 10 to 85% relative humidity (non-condensing) No moving parts permits use in high dust / particulate / vibration environments.
<b>Reliability</b>	> 100,000 h
<b>Certifications</b>	FCC Class A&B, CE, CCC, RoHS compliant, BIS, NOM, ISO 9001:2015, ISO 14001:2015
<b>User Software</b>	Management Software: vCloudPoint's vMatrix Server Manager with Dynamic Desktop Protocol (DDP); Optional vMatrix Classroom Control at additional cost.
<b>Supported Operating System</b>	Microsoft Windows XP SP3 Pro 32bits, 7, 8 ,8.1 & 10 (excluding Starter, Home Basic and Insider editions), Server 2003 32 bits, 2008R2, 2012, 2012R2, 2016, Multipoint Server 2011, 2012. Windows 11 pro & Windows server 2019 & 2022